



Give It Gas - operates solely as an ONLINE BUSINESS

Tel: (011) 646 9439

Cell: (082) 452 4488

Email: [penny@giveitgas.co.za](mailto:penny@giveitgas.co.za)

[www.giveitgas.co.za](http://www.giveitgas.co.za)

## COLD FACTOR 120LITRE GAS/ ELECTRIC CHEST FREEZER (CF120GE/ CF120GES)



Packaged dimensions : 825mm (H) x 685mm (W) x 680mm (D)

Actual dimensions : 805mm (H) x 655mm (W) x 650mm (D)

Weight : 40kg

CF120GE – White Chromadek with Textradek Lid / CF120GES – Stainless Steel

Energy sources: LP Gas & 220v Electricity

Wattage (W) : 200W

Gas Consumption/ 24 hour : 600g (approx) i.e. 1 x 9 kg gas bottle will last approximately 18 – 21 days.

Electricity Consumption/ 24 hour: 0.22Kwh

-12°C @ +32°C

Freezers are capable of freezing to 44°C below ambient. Example: At 32°C ambient (outside temperature) the freezer's interior temperature will be -12°C. At 20°C ambient (outside temperature), the freezer's interior temperature will be -20°C .

Capable of freezing 2kg of water in 24 hours while keeping everything else frozen.

Freezers are equipped with a gas safety valve which cuts off the gas flow to the burner (in less than 60 seconds) in the event of the burner flame going out.

Gas Thermostat (optional extra). Gas thermostat will allow unit to be used as a fridge instead of a freezer.

Metal Hinges

Absorption unit covered

Gas Hose & Regulator included

Basket x 1

Freezers have 75mm foam insulation, significantly increasing the cold hold-over time, compared to other freezers, when not switched on.

No moving parts inside the Absorption System, making repair and maintenance inexpensive.

Freezers are level sensitive and proper levelling must be done when stationary.